



### Thermic 2W 9 H Thermic 2W 13 L Thermic 2W 13 H

**NEW**



#### Equipped with:

- Honda GX and Loncin gasoline engines
- Self-priming triplex pump with **Pressure Booster**, 3 ceramic pistons, brass pump head and built-in unloader valve
- Unleaded gasoline engine 9 HP **Honda GX 270** (Thermic 2W 9 H)
- Unleaded gasoline engine 13 HP **Loncin G 390F** (Thermic 2W 13 L)
- Unleaded gasoline engine 13 HP **Honda GX 390** (Thermic 2W 13 H)
- 5 litres detergent tank with filter and cap • Readily serviceable suction water filter
- Oil-alert safety device for engine protection • Glycerine pressure gauge.
- Ø 300 big pneumatic wheels; easy to handle also up and down steps and over uneven ground • S/S pump cover on request

#### Standard equipment:

- 0.966.0083 Gun M22 - 3/8 with rotating coupling.



- 0.966.0084 Lance M22 high/low pressure



- 3.103.0197 Nozzle type (Thermic 2W 9 H)
- 3.103.0196 Nozzle type (Thermic 2W 13 L) (Thermic 2W 13 H)



- 0.966.0091 High pressure hose 10 m



#### Optional:

- Hose reel kit cod. 0.966.0062 hose included (15 m)
- 0.966.102 ROTOX lance (Thermic 2W 9 H)
- 0.966.0101 ROTOX lance (Thermic 2W 13 L) (Thermic 2W 13 H)
- 5.012.0319 Suction hose with check valve

	Thermic 2W 9 H	Thermic 2W 13 L	Thermic 2W 13 H
code	0.066.0033	0.066.0035	0.066.0034
operat. pressure	210 bar-3045 psi	290 bar-4206 psi	290 bar-4206 psi
delivery rate	900 l/h-3.96 GPM	900 l/h-3.96 GPM	900 l/h-3.96 GPM
engine type/hp	Honda GX 270/9	Loncin G 390F/13	Honda GX 390/13
pump type/RPM	CL 4.5/3400 RPM	CL 4.5/3400 RPM	CL 4.5/3400 RPM
max. water inlet temp.	60 °C	60 °C	60 °C
dimension/weight	85x58x105cm / 48 Kg - 105 lbs	85x58x105cm / 51 Kg - 112 lbs	85x58x105cm / 51 Kg - 112 lbs