



DOCTOR CHARGE 50



Overview

DOCTOR CHARGE 50

cod. 807613

Multifunctional, electronic battery charger (BATTERY MANAGER) for complete maintenance of WET, GEL, AGM, MF, PbCa, EFB, Li 6V/12V/24V batteries and for support activities in interventions, including diagnostics, on vehicles carried out in workshops, body shops and dealers.

The Pulse Tronic technology guarantees optimal battery charging over 8 phases.

Features:

- Automatic charging and maintenance in Pulse Tronic based on the technology of the selected battery;
- BOOST function for quick charge;
- COLD function for charging and maintenance of batteries at low temperatures;
- stable POWER SUPPLY for diagnostics (BSU) when changing the battery (SUPPLY) and maintain the battery health of vehicles on display in showrooms;
- Batteries maintenance through RECOVERY function, to recover sulphated or very low batteries; and EQUALIZATION function to restore optimal functionality with periodic regeneration;
- TESTER for checking terminal voltage, starting capacity (CCA) and vehicle alternator operation;
- Start aid;
- Cable extension compensation function;
- LCD display;
- Protection against overcharge, short circuit and polarity reversal.

Fit with PFC device.

Complete with cable with clamps.

Telwin SPA | Via della Tecnica 3 - 36030 VILLAVERLA (VI) ITALY - Tel. +39-0445-858811 - Fax +39-0445-858800/801 - www.telwin.com

Jan 16, 2023



DOCTOR CHARGE 50



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 807613	A_{EFF}	EFFECTIVE CHARGING CURRENT 45 / 45 / 23 A	C_{MAX}	MAX RATED REFERENCE CAPACITY 600 A
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	A_{EN}	RATED CHARGE CURR. EN60335-2-29 40 / 40 / 20 A	IP	PROTECTION DEGREE IP33
F	MAINS FREQUENCY 50 / 60 Hz	A_{1V/C}	START CURRENT 1V/C EN60335-2-29 40 (Boost) A	W H L	DIMENSIONS 9,2x20x33 cm
P	CHARGING ABSORBED POWER 610 W	C_{MIN}	MIN. RATED REFERENCE CAPACITY 10 Ah	kg	WEIGHT 3,77 kg
BATTERY	CHARGING VOLTAGE 6 / 12 / 24 V				

Included Accessories

CLAMPS PATCH CORD - 125278